



TURBO CART 96



The Turbo Cart 96 is designed to clean larger components where higher low rates are required. Our standard model comes with all the “bells and whistles” that others charge for.

Features:

- Leeson Duck motor 1 hp, 115/230V 60 Hz motor
- Finish Thompson 3450 rpm magnetic drive pump
- Triple set of gauges to monitor the entire cleaning process
- Gauge Guards to prevent gauge damage from chemicals
- In-line check valve to prevent any back flow flooding.
- True Union in-line ball valves
- By-pass valve to regulate flow rates from 1 -96+ gpm with 50' head
- 2 - 25' inlet/outlet hose, 10' suction, all hoses are reinforced chemical hoses
- 55-gallon on-board tank with drain and large 6" access for filling, venting, and cleaning.
- Y-strainer for filtering out solids and sampling test port to monitor pH levels
- 25' GFCI power cord
- On/Off indicator light
- Cast iron 8" smooth rolling, cast iron core HD wheels with 8" smooth rolling polyurethane coated wheels with "full range" maneuverability when needed.
- Also available with a pneumatic pump



Applications:

- Industrial Descaling Applications
- Heat Exchangers
- Boilers
- Plate and Frame Heat Exchangers
- Chillers/Absorbers
- Cooling Towers
- Medium size Condensers

Contact us for more information
or to place an order

Ken Marko

800-567-1443

kenm@wheelhouseindustries.com

www.WheelHouseIndustries.com

WHEELHOUSE
INDUSTRIES LLC